

BD-1530

Area Imaging **Scanner**

Functional

Reliable

Economical

Handheld



Economical High Performance

BD-1530 delivers aggressive scan performance on all linear barcodes and 2D codes. It provides fast and reliable scanning performance. It's ergonomic design and available with multiple interfaces that changes interface by replacing cable.

BD-1530 is valued product of general purpose cabled scanner. It's perfect for using in retail, document/billing process and banking/finance environment, health care, medical industry.



Reading
1D & 2D
codes

3 mil
1D

640(H) x
480(V)
pixels


Multiple
interfaces

120 FPS


BD-1530

Area Imaging Scanner

Dimensions



Unit: mm



Typical Performance

Narrow Width	Depth of Field
Code 39	3 mil 35 mm – 90 mm
EAN-13	13 mil 45 mm – 180 mm
Data Matrix	6.67 mil 45 mm – 90 mm
QR Code	6.67 mil 60 mm – 90 mm

Resolution: 3 mil 1D, 6.67mil 2D
Performance may be impacted by bar code quality and environmental conditions

General

Interface	USB-KB / USB-COM / RS-232
Barcodes Supported (1D)	UPC-A, UPC-E, EAN-13, EAN-8, Code 128, GS1-128, Code-39, Code-32, Code-93, Pharmacode, Codabar/NW7, MSI, Interleaved 2 of 5, GS1 DataBar-14, GS1 DataBar Stacked, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked, Composite Component A / B / C
Barcodes Supported (2D)	PDF 417, MicroPDF 417, QR Code, Micro QR Code, Data Matrix, Aztec, Maxi Code, Dot Code

Optical

Optical System	640 (H) x 480 (V) pixels
Light Source	Aiming 610nm red LED + Illumination 6000-6500k white LED
Resolution	3 mil (Code 39), 6.67 mil (Data Matrix, QR Code)
Frame Rate	120 FPS
Field of View	Horizontal: 28°; Vertical: 36°
PCS	30%
Indicator	Beeper and LED

Electrical

Voltage	DC 5V
Scanning Currents	130 mA
Standby Currents	95 mA

Environment

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	10% - 95% RH (Non-condensing)
Storage Humidity	10% - 85% RH (Non-condensing)
Drop	1.5m drops
Light Levels	100,000 lux

Physical

Weight	182g(w/cable)
Dimensions	173.3mm (L) x 69.7mm (W) x 72.6mm (H)
Housing Material	ABS plastic
Cable	Length: 5ft (150cm) / USB Type: A or C, RS-232
Warranty	1 year
Certificate	CE / FCC

V1-210700 This information is subject to change without prior notice.