

Feature

- ◆ Support 1D barcodes and GS1 DataBar and GS1 Stacked codes.
- ◆ Reading speed up to 270 scans/sec.
- ◆ Presentation scanning



Typical Performance	
CODE 39	4 mil 20 mm - 50 mm
CODE 39	5 mil 15 mm - 70 mm
CODE 39	10 mil 19 mm - 85 mm
EAN-13	13 mil 15 mm - 125 mm

Specifications

General	
Interface	USB-KB / USB-COM / RS-232
Barcodes supported (1D)	All UPC/ EAN/JAN, EAN 128 Code, Code 39, Code 39 Full ASCII, Code 32/ Italian Pharmacy, Code 128, CODABAR/NW7, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI/Plessey, Telepen, Code 93, Code 11, China Postage, GS1 Databar,
Optical	
Optical Sensor	2500 pixels
Light Source	Red LED (660nm)
Resolution	4 mil
Scan Rate	270 scans/sec
PCS	30%
Electrical	
Voltage	DC 5V
Scanning Currents	50 mA
Scanning Currents	30 mA
Environment	
Operating Temperature	-20°C to 55°C (-4°F to 131°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	10% - 95% RH (Non-condensing)
Storage Humidity	10% - 85% RH (Non-condensing)
Drop	1.5m drops
Physical	
Weight	132g
Dimensions	164.5mm (D) x 71.7 mm (W) x 36.2mm (H)
Housing Material	ABS plastic
Cable Length	5ft (150cm)

V1-210800 This information is subject to change without prior notice.